CHECK SHEET

Title page 1 and Pages 1 to 170 are effective as of the date shown. Original and revised pages as named below contain all changes from the original tariff that are in effect on the date hereof.

	Number of Revision Except as		Number of Revision Except as		Number of Revision Except as
Page	Indicated	Page	<u>Indicated</u>	<u>Page</u>	<u>Indicated</u>
1	3rd Revised*	· <u> </u>			·
3	3rd Revised*				
6	3rd Revised*				
7	3rd Revised*				
8	3rd Revised*				
9	3rd Revised*				
30	3rd Revised*				
31	3rd Revised*				
32	3rd Revised*				
66	3rd Revised*				
79	3rd Revised*				
83	3rd Revised*				
88	3rd Revised*				
98	3rd Revised*				
99	3rd Revised*				
103	3rd Revised*				
104	3rd Revised*				
110	3rd Revised*				
115	3rd Revised*				
116	3rd Revised*				
117	3rd Revised*				
120	3rd Revised*				
128	3rd Revised*				
129	3rd Revised*				
143	3rd Revised*				
158	3rd Revised*				
159	3rd Revised*				
160	3rd Revised*				
165	3rd Revised*				

^{*} New or Revised Page

	TABLE OF CONTENTS (Cont'd)	<u>Page</u>		
	2.3.2 Ownership of Facilities and Theft 2.3.3 Reserved for Future Use	25	25	
	2.3.4 Reserved for Future Use	26	23	
	2.3.5 Reserved for Future Use	27		
	2.3.6 Availability for Testing	28		
	2.3.7 Balance	28		
	2.3.8 Design of Customer Services	28		
	2.3.9 Reference to KINI Network	28		
	2.3.10 Reserved for Future Use	28		
	2.3.11 Claims and Demands for Damages	20	29	
	2.3.12 Coordination with Respect to		۷)	
	Network Contingencies	30		
	2.3.13 Jurisdictional Report Requirements	30		(C)
	2.3.14 Determination of Interstate Charges	30		(C)
	for Mixed Interstate and			
	Intrastate Access Service	36		
2.4	Payment Arrangements and Credit Allowances	36		
	2.4.1 Payment of Rates, Charges and Deposits 2.4.2 Minimum Periods	36	40	
	2.4.3 Cancellation of an Order for Service	40		
	2.4.4 Credit Allowance for Service			
	Interruptions	41		
	2.4.5 Title or Ownership Rights	44		
	2.4.6 Rating and Billing of Access Services Provided by KINI and Routing			
	Exchange Carriers	44		
2.5	Connections	45		
	0.5.1	4 -		
	2.5.1 General	45		
2.6	<u>Definitions</u>	45		
	Access Code	45		
	Access Minutes	46		
	Access Tandem	46		
	Answer/Disconnect Supervision	46		
	Attenuation Distortion	46		
	Balance (100 Type) Test Line		46	
	Bit	46		

Tariff F.C.C. No. 1 3rd Revised Page 6 Cancels 2nd Revised Page 6

VIRTUAL EQUAL ACCESS SERVICE

		TABLE OF CONTENTS (Cont'd)	<u>Page</u>		
5.	ORDER	ING OPTIONS FOR SWITCHED ACCESS SERVICE	63		
	5.1	<u>General</u>	63		
		5.1.1 Ordering Conditions 5.1.2 Provision of Other Services 5.1.3 Reserved for Future Use	63 64 66		
	5.2	Access Order	66		(C)
		5.2.1 Access Order Date Intervals 5.2.2 Access Order Modifications 5.2.3 Cancellation of an Access Order 5.2.4 Selection of Facilities for Access Orders 5.2.5 Minimum Period 5.2.6 Minimum Period Charges 5.2.7 Reserved for Future Use	68 70 74 76 76 77		
	5.3	Available Inventory	78		
	5.4	Access Orders for Services Provided By KINI and Exchange Telephone Companies	78		(C)
6.	SWIT	CHED ACCESS SERVICE	82		
	6.1	<u>General</u>	82		
		6.1.1 Feature Group Arrangements and Manner of Provision 6.1.2 Reserved for Future Use 6.1.3 Rate Categories 6.1.4 Design Layout Report 6.1.5 Acceptance Testing 6.1.6 Routine Testing 6.1.7 Ordering Options and Conditions	82 85 86 91 91 92	91	(C)
	6.2	Provision and Description of Switched Access Service Feature Groups	92		
		6.2.1 Feature Group A (FGA) 6.2.2 Reserved for Future Use 6.2.3 Reserved for Future Use 6.2.4 Reserved for Future Use	93 99 100 101		(D)
		6.2.5 Feature Group D (FGD)	102		(D)

Issued: September 24, 1999 Effective: October 9, 1999

Robert Mater, Director Engineering Operations 621 Westport Boulevard Salina, Kansas 67401

Tariff F.C.C. No. 1 3rd Revised Page 7 Cancels 2nd Revised Page 7 VIRTUAL EQUAL ACCESS SERVICE

	TABLE OF CONTENTS (Cont'a)	<u>Page</u>
6.4	Transmission and Specifications	107
	6.4.1 Standard Transmission Specifications 6.4.2 Data Transmission Parameters	107 111

6.4	Transmission and Specifications	107	
	6.4.1 Standard Transmission Specifications 6.4.2 Data Transmission Parameters	107 111	(C)
6.5	Obligations of KINI	114	
	6.5.1 Network Management 6.5.2 Design and Traffic Routing of	114	
	Switched Access Service 6.5.3 Provision of Service Performance	114	
	Data	115	
	6.5.4 Trunk Group Measurement Reports 6.5.5 Determination of Number of	115	
	Transmission Paths	115	(C)
	6.5.6 Reserved for Future Use	116	
	6.5.7 Design Blocking Probability	116	(C)
6.6	Obligations of the Customer	118	
	6.6.1 Report Requirements	118	
	6.6.2 Supervisory Signaling	119	
	6.6.3 Trunk Group Measurement Reports	119	
	6.6.4 Design of Switched Access Services 6.6.5 Short Duration Mass Calling	119	
	Requirements	119	
6.7	Rate Regulations	120	
	6.7.1 Description and Application of		
	Rates and Charges	120	(C)
	6.7.2 Minimum Period	124	
	6.7.3 Reserved for Future Use	124	
	6.7.4 Reserved for Future Use	125	
	6.7.5 Reserved for Future Use	126	
	6.7.6 Reserved for Future Use	127	(<)
	6.7.7 Measuring Access Minutes	128	(C)
	6.7.8 Network Blocking Charge for Feature Group D	130	
6.8	Rates and Charges	132	
	6.8.1 Switched Access	132	
ותטשת	OTTED EOD ELIMITE LIGE	1 2 2	

7. 133 RESERVED FOR FUTURE USE

Issued: September 24, 1999

Effective: October 9, 1999

Robert Mater, Director Engineering Operations 621 Westport Boulevard Salina, Kansas 67401

		TABLE OF CONTENTS (Cont'd)	<u>Page</u>	
8.	CUSTO	MER'S POINT OF TERMINATION INFORMATION	134	
	8.1	General Information	134	
	8.2	Customer's Point of Termination	134	
9.	ROUTI	NG EXCHANGE CARRIERS	135	
	9.1	Exchanges and Localities	135	
10.	OTHER	ROUTING CELLULAR CARRIERS	136	
11.	RESER	VED FOR FUTURE USE	137	
12.	RESER	VED FOR FUTURE USE	138	
13.		IONAL ENGINEERING, ADDITIONAL LABOR	139	
	13.1	Additional Engineering	139	
		13.1.1 Charges for Additional Engineering	140	
	13.2	Additional Labor	141	
		13.2.1 Overtime Installation 13.2.2 Overtime Repair 13.2.3 Stand By 13.2.4 Testing and Maintenance with Exchange Telephone Companies 13.2.5 Other Labor	141 141 141 141 141	
		13.2.6 Charges for Additional Labor	142	(I)
	13.3	Miscellaneous Services	143	
		13.3.1 Maintenance of Service 13.3.2 Reserved for Future Use 13.3.3 Reserved for Future Use 13.3.4 Testing Services 13.3.5 Provision of Access Service Billing Information	143 144 145 146	
14.	RESER	VED FOR FUTURE USE	151	
15.	<u>INTE</u> R	FACE GROUPS, TRANSMISSION SPECIFICATIONS		

Tariff F.C.C. No. 1 3rd Revised Page 9 Cancels 2nd Revised Page 9

VIRTUAL EQUAL ACCESS SERVICE

	TABLE OF CONTENTS (Cont'd)	<u>Page</u>	
15.1	Switched Transport Interface Groups	152	
	15.1.1 Interface Group 1 15.1.2 Interface Group 2 15.1.3 Interface Group 3 15.1.4 Interface Group 4 15.1.5 Interface Group 5 15.1.6 Interface Group 6 15.1.7 Interface Group 7 15.1.8 Interface Group 8 15.1.9 Interface Group 9 15.1.10 Interface Group 10 15.1.11 Available Premises Interface Codes 15.1.12 Supervisory Signaling	152 153 153 154 154 155 155 156 156 157 158	
15.2	Transmission Specification Switched Access Service	162	
	15.2.1 Standard Transmission Specification 15.2.2 Data Transmission Parameters		(C)

- 2. General Regulations (Cont'd)
 - 2.3 <u>Obligations of the Customer</u> (Cont'd)
 - 2.3.11 Claims and Demands for Damages (Cont'd)
 - (D) The customer shall defend, indemnify and save harmless KINI from and against any suits, claims, losses or damages, including punitive damages, attorneys' fees and court costs by the customer or third parties arising out of any act or omission of the customer in the course of using services provided under this tariff.
 - 2.3.12 Coordination with Respect to Network Contingencies

The customer shall, in cooperation with KINI, coordinate in planning the actions to be taken to maintain maximum network capability following natural or man-made disasters which affect telecommunications services.

- 2.3.13 Jurisdictional Report Requirements
 - (A) Jurisdictional Reports
 - (1)(a) When a customer orders Feature Group (C)

A Switched Access Service, the
Customer shall state in its order the
projected interstate percentage for
interstate usage for each Feature
Group A Switched Access Service
group ordered. The term group shall
be construed to mean single lines or
trunks as well. (C)

(b)

- 2. General Regulations (Cont'd)
 - 2.3 <u>Obligations of the Customer</u> (Cont'd)
 - 2.3.13 <u>Jurisdictional Report Requirements</u> (Cont'd)
 - (A) Jurisdictional Reports (Cont'd)

(1)(b) (D)

- (c) The projected interstate percentages will be used by KINI to apportion the usage between interstate and intrastate until a revised report is received as set forth in (7) following.
- (2) All single Feature Group A Switched
 Access Service usage and charges will be apportioned by KINI between interstate
 and intrastate. The projected

percentage reported as set forth in 1(a) and 1(b) preceding will be used to make such apportionment.

(3) For multiline hunt group arrangements where either the interstate or the intrastate charges are based on measured usage, the interstate Feature Group A Switched Access Service(s) information reported as set forth in (1) preceding will be used to determine the charges as follows:

For all groups the number of access minutes for a group will be multiplied by the projected interstate percentage to develop the interstate

access minutes. The

interstate

number of access minutes for the group (C)

- 2. General Regulations (Cont'd)
 - 2.3 <u>Obligations of the Customer</u> (Cont'd)
 - 2.3.13 <u>Jurisdictional Report Requirements</u> (Cont'd)
 - (A) <u>Jurisdictional Reports</u> (Cont'd)
 - (3) (Cont'd)

minus the developed interstate access (C) minutes for the group will be the developed intrastate access minutes. (C)

(4) When a customer orders Feature Group D
Switched Access Service, KINI, where the
jurisdiction can be determined from the call
detail, will, unless the customer provides
the projected interstate percentage for
interstate usage for each end office group
in its order, determine the projected interstate percentage as follows:

For originating access minutes, the projected interstate percentage will be developed on a

monthly basis by end office

when the Feature Group D Switched Access

Service access minutes are measured by

dividing the measured access minutes (the access the calling

minutes where

interstate originating

number is in one state and the

called number is in another state) by the

total originating access minutes call detail is

when the

adequate to determine the

appropriate jurisdiction. For terminating

access minutes, the data used by KINI to

develop the projected

interstate percentage minutes will be used interstate percentage

for originating access to develop projected

for such terminating access minutes. When

originating call details are insufficient

Issued: September 24, 1999 Effective: October 9, 1999

Robert Mater, Director Engineering Operations 621 Westport Boulevard Salina, Kansas 67401

to determine the the customer shall

jurisdiction for the call, supply the projected interstate percentage or authorize

KINI to use the KINI developed percentage. This percentage shall be used by KINI as the interstate percentage for such call detail. KINI will designate the number obtained by subtracting the

projected interstate

5. Ordering Options for Switched Access Service (Cont'd)

5.2 Access Order

An Access Order is used by KINI to provide to a customer Access Service as follows:

- Switched Access Services as set forth in Section 6. following.
- Other Services as set forth in Section 5.1.2 preceding.

When placing an order for Access Service, the customer shall provided, at the minimum, the

following information:

- For Feature Group A Switched Access Service, the customer shall specify the number of lines and the first point of switching (i.e., dial tone office), the Local Transport options and Local Switching options desired. In addition, the customer shall specify whether the ordered line(s) is for FX/ONAL service or MTS/WATS-type service. If the customer specifies MTS/WATS-type service, it shall also specify which lines are to be arranged in multiline hunt group arrangements and which lines are to be provided as single lines.

(D)

(D)

- For Feature Group D Switched Access Service, the customer shall specify the number of busy hour minutes of capacity (BHMC) or trunks needed to carry traffic from the end office of a Routing Exchange carrier set forth in Section 9. following to KINI's central access tandem by type of BHMC

- 5. Ordering Options for Switched Access Service (Cont'd)
 - 5.4 <u>Access Orders for Services Provided by KINI and Exchange</u> Telephone Companies (Cont'd)
 - (A) (Cont'd)
 - (1) When Switched Access Services are ordered to KINI's central access tandem, the customer will place the order with KINI. The customer must also supply a copy of the order to each Exchange Telephone Company involved in providing the service and subtending KINI's central access tandem.
 - (2) When Switched Access Services are ordered to a point of termination listed in Section 8. following other than KINI's central access tandem, the customer will place the order as follows:

(a)

(D)

- (b) For Feature Groups A and D Switched Access Service, the customer must place the order with the Exchange Telephone Company in whose territory the end office is located. The customer must also supply a copy of the order to KINI.
- (3) For the Switched Access Services ordered set forth in (1) and (2) preceding, the customer must also supply a copy of the order to the Exchange Telephone Company in whose operating territory a customer premises is located and any other Exchange Telephone Company involved in providing the service.
- (4) For initiation, additions, changes or deletions to the Interim NXX Translation code(s), the customer must place an order with the carrier who provides the Interim NXX Translation. The customer must also provide a copy of the order to the Exchange Telephone Companies subtending the Interim NXX Translation office.

- 6. Switched Access Service (Cont'd)
 - 6.1 <u>General</u> (Cont'd)
 - 6.1.1 <u>Feature Group Arrangements and Manner of Provision</u> (Cont'd)
 - (B) <u>Feature Group A (FGA)</u>

FGA Access, which is available to all customers, provides line side access to KINI's end

office

switches with an associated seven digit local telephone number for the customer's use in originating communications from and terminating communications to an Interexchange Carrier's Interstate Service or a customer - provided interstate communications capability.

The customer must

specify the Interexchange Carrier to which the FGA service is connected or, in the alternative, specify the means by which the FGA access communications is transported to another state.

(C)

(D)

(D) <u>Feature Group D (FGD)</u>

FGD Access, which is available to all customers, provides trunk side access at a

customer's point of

interconnection with an associated uniform 10XXX

access code for the customer's use in originating and terminating communications unless a Routing

Exchange Carrier's end office is unable to a uniform 10XXX code.

provide

(E) Reserved for Future Use.

- 6. Switched Access Service (Cont'd)
 - 6.1 <u>General</u> (Cont'd)
 - 6.1.3 <u>Rate Categories</u> (Cont'd)
 - (A) <u>Switched Access</u> (Cont'd)
 - (2) <u>Nonchargeable Optional Features</u> (Cont'd)
 - (a) <u>Supervisory Signaling</u> (Cont'd)

version is required by the customer to meet its signaling capa-

bility, the

customer may order an

optional supervisory signaling arrangement for each transmission path provided as follows:

Interface Group 6 may, at the option of the customer, be provided with individual transmission path SF supervisory signal-

ing where such

signaling is

available in KINI's central access tandem. Generally, such signaling is available only where KINI's central access tandem provides an analog, i.e., non-digital, interface and a a portion of the facility provided by the customer between KINI's central access tandem and the customer's premises is analog.

(b)

(D)

Issued: September 24, 1999

Effective: October 9, 1999

Robert Mater, Director Engineering Operations 621 Westport Boulevard Salina, Kansas 67401

- 6. Switched Access Service (Cont'd)
 - 6.2 <u>Provision and Description of Switched Access Service</u> Feature Groups (Cont'd)
 - 6.2.1 <u>Feature Group A (FGA)</u> (Cont'd)
 - (D) (Cont'd)
 - in 6.1.6 preceding which are included with the installation of service and as ongoing routine testing, Additional Cooperative Acceptance Testing and Additional Manual Testing are available as set forth in 13.3.5 following.
 - 6.2.2 Reserved for Future Use

(D)

Tariff F.C.C. No. 1 3rd Revised Page 99 Cancels 2nd Revised Page 99

VIRTUAL EQUAL ACCESS SERVIEC

- 6. <u>Switched Access Service</u> (Cont'd)
 - 6.2 <u>Provision and Descrition of Switched Access Service</u> <u>Feature Groups</u> (Cont'd)
 - 6.2.2 Reserved for Future Use.

(D)

- 6. Switched Access Service (Cont'd)
 - 6.2 <u>Provision and Description of Switched Access Service Feature</u> Groups (Cont'd)
 - 6.2.5 Feature Group D (FGD) (Cont'd)
 - (A) <u>Description</u> (Cont'd)
 - (4) (Cont'd)

(DIAL-IT) Network Services. Additionally, non-access charges will also be billed for calls from a FGD trunk to another customer's service in accordance with the customer's applicable service rates when KINI performs the billing function for that

customer.

Calls in the terminating direction will not be completed to 950-OXXX or 950-1XXX access codes, local operator assistance (O- and O+), and 10XXX access codes. FGD may not be switched, in the terminating direction, to Switched Access Service Feature Groups A or D.

(C)

The customer will also be billed access charges by Routing Exchange Carriers and other Exchange Telephone Companies for the provision of access service in their operating territories between a KINI premises listed in Section 8. following and the end offices served by KINI's central access tandem.

(5) FGD switching will be arranged to accept calls from the telephone exchange service locations without the need for dialing the 10XXX uniform access code. Each telephone exchange service line may be marked with a code to identify to which 10XXX code its calls will be directed for interLATA service. The access code for FGD switching is a uniform access code of the form 10XXX

unless a Routing Exchange Carrier's end office switch is unable to provide a uniform 10XXX code. A single access code will be the assigned number of all FGD access provided to the customer by KINI. No access code is

- 6. Switched Access Service (Cont'd)
 - 6.2 <u>Provision and Description of Switched Access Service Feature</u> Groups (Cont'd)
 - 6.2.5 <u>Feature Group D (FGD)</u> (Cont'd)
 - (A) <u>Description</u> (Cont'd)
 - (5) (Cont'd)

required for calls to a customer over FGD Switched Access Service if the end user's telephone exchange service is arranged for presubscription to that customer. Where no access code is required, the number dialed by the end user shall be a seven (7) or ten (10) digit number, where appropriate, for calls in the North American Numbering Plan (NANP). The form of the numbers dialed by the end user is NXX-XXXX, 0 or 1 + NXX-XXXX, NPA+ NXX-XXXXX, 0 or 1 + NPA + NXX - XXXXX, and for International Direct Distance Dialing (IDDD), 01 + CC + NN or 011 + CC + NN

The end offices of the Routing Exchange Carriers that are listed in Attachment 1 are unable to provide a uniform 10XXX code.

(6)

- 6. Switched Access Service (Cont'd)
 - 6.4 <u>Transmission Specifications</u> (Cont'd)
 - 6.4.1 <u>Standard Transmission Specifications</u> (Cont'd)
 - (B) Type B Transmission Specifications (Cont'd)
 - (4) <u>C-Notched Noise</u>

The maximum C-Notched Noise, utilizing a -16 dBmO holding tone is less than or equal to 47 dBrnCO.

(5) <u>Echo Control</u>

Echo Control is identified as Equal (
Level Echo Path Loss for FGD, and expressed as Echo Return Loss (ERL) and
Singing Return Loss (SRL). The ERL and SRL
also differ by Feature Group. They are
greater than or equal to the following:

Echo Return	Singing Return	
Loss	Loss	
8dB	4 dB	(C)

(C) Reserved for Future Use.

6. Switched Access Service (Cont'd)

6.5 Obligation of KINI (Cont'd)

6.5.2 <u>Design and Traffic Routing of Switched Access Service</u> (Cont'd)

Finally, KINI will decide whether trunk side access will be provided through the use of two-wire or four-wire trunk terminating equipment. Selection of facilities and equipment and traffic routing of the service are based on standard engineering methods, available facilities and equipment, and the KINI traffic routing plans.

If the customer desires routing or directionality different from that determined by KINI, KINI will work cooperatively with the customer in determining the directionality of the service.

6.5.3 Provision of Service Performance Data

Subject to availability, end-to-end service performance data available to KINI through its own service evaluation routines, may also be made available to the customer based on previously arranged intervals and format. These data provide information on overall end-to-end call completion and noncompletion performance, e.g., customer equipment blockage, failure results and transmission performance. These data do not include service performance data which are provided under other tariff sections, e.g., testing service results. If data are to be provided in other than paper format, the charges for such exchange will be determined on an individual case basis.

6.5.4 Trunk Group Measurement Reports

Subject to availability, KINI will make available trunk group data in the form of usage in CCS, peg count and overflow, to the customer based on previously agreed to intervals.

6.5.5 Determination of Number of Transmission Paths

KINI will determine the number of Switched Access (C)
Service transmission paths to be provided for the
Switched Access Feature Groups ordered. A transmission path is a derived communication path of

a (C)

- 6. Switched Access Service (Cont'd)
 - 6.5 Obligations of KINI (Cont'd)
 - 6.5.5 <u>Determination of Number of Transmission Paths</u>(Cont'd)

frequency bandwidth of approximately 300 Hz to 3000 Hz provided over a high speed digital facility between a customer's point of interconnection listed in Section 8. following and KINI's central access tandem. The number of transmission paths will be developed using the total busy hour minutes of capacity by type (as

described in 6.1.1 (F) preceding) for each
Feature Group ordered to KINI's central
access tandem. The total busy hour
minutes of capacity by type for the Feature

Group will be converted to transmission paths

using standard traffic engineering methods. (C)

6.5.6 Reserved for Future Use.

- 6. Switched Access Service (Cont'd)
 - 6.5 <u>Obligations of KINI</u> (Cont'd)
 - 6.5.7 Design Blocking Probability

KINI will design the facilities used in the provision of Switched Access Service to meet the blocking probability criteria as set forth in (A) through (D) following.

(A)

- (B) For Feature Group D, the design blocking objective will be no greater than one percent (1%) between the customer's point of interconnection set forth in Section 8. following and KINI's central access tandem. Standard traffic engineering methods as set forth in reference document Telecommunications
 Networks
 Transmission Engineering Volume 3 Networks
 Transmission Engineering Volume 3 Networks
 Transmission Engineering Volume 3 Networks
 Transmission Engineering Volume 3 Networks
 Transmission Engineering Volume 3 Networks
 Transmission Engineering Volume 3 Networks
 Transmission Engineering Volume 3 Networks
 Transmission Engineering Volume 3 Networks
 Transmission Engineering Volume 3 Networks
 Transmission Engineering Volume 3 Networks
 Transmission Engineering Volume 3 Networks
 <a href="Transmission Engineering Volume 3 -
- (C) KINI will perform routine measurement functions to assure that an adequate number of transmission paths are in service. KINI will recommend that additional busy hour minutes of capacity be ordered by the customer when additional paths

required to reduce the measured blocking to the design blocking level. For the capacity ordered, the design blocking objective is assumed to have been met if the routine measurements show that the measured blocking does not exceed the threshold listed in the following table.

are

6. <u>Switched Access Service</u> (Cont'd)

6.7 <u>Rate Regulations</u>

This section contains the specific regulations governing the rates and charges that apply for Switched Access Service.

6.7.1 Description and Application of Rates and Charges

There are two types of rates and charges that apply to Switched Access Service. These are usage rates and nonrecurring charges.

(A) <u>Usage</u>

Switched Access Usage Rates are rates that apply only when a specific rate element is used. These rates are applied on a per access minute basis. Usage rates are accumulated over a monthly period.

(B) Nonrecurring Charges

Nonrecurring charges are one-time charges that apply for a specific work activity (i.e. installation or change to an existing service). The types of nonrecurring charges that apply for Switched Access Service Are: installation of service, Interim NXX Translation Optional feature, and service rearrangements.

(1) Installation of Service

Nonrecurring charges apply to each
Switched Access Service installed.
For FGD, which is ordered on a Busy
Hour Minutes of Capacity or trunk basis,
the charge is applied on a per trunk
basis but the charge applies only
the capacity ordered requires the
installation or activation of an
additional trunk(s) which is
identified for the sole use of the

(C)

when

uniquely

Issued: September 24, 1999

4,1999 Effective: October 9, 1999
Robert Mater, Director
Engineering Operations

621 Westport Boulevard Salina, Kansas 67401

(C)

VIRTUAL EQUAL ACCESS SERVICE

- 6. Switched Access Service (Cont'd)
 - 6.7 <u>Rate Regulations</u> (Cont'd)
 - 6.7.7 Measuring Access Minutes

Customer traffic to and from end offices of the Routing Exchange Carriers set forth in Section 9. following will be measured (i.e., recorded) by KINI at its central access tandem. Originating and terminating calls will be measured (i.e., recorded) by KINI to determine the basis for computing chargeable access minutes. In the event the customer message detail is not available because KINI lost or damaged tapes or incurred recording system outages, KINI will estimate the volume of lost customer access minutes of use based on previously known values. For terminating and for originating calls over FGD, the measured minutes are the chargeable access minutes. (C)

FGD access minutes or fractions thereof, the exact value of the fraction being a function of the switch technology where the measurement is made, are accumulated over the billing period for each end office, and are then rounded up to the nearest access minute for each end office.

(A) Reserved for Future Use.

Effective: October 9, 1999

Issued: September 24, 1999

- 6. <u>Switched Access Service</u> (Cont'd)
 - 6.7 <u>Rate Regulations</u> (Cont'd)
 - 6.7.7 <u>Measuring Access Minutes</u> (Cont'd)

(B)

(C) Reserved for Future Use.

13. <u>Additional Engineering</u>, <u>Additional Labor and Miscellaneous</u> Services (Cont'd)

13.2 <u>Additional Labor</u> (Cont'd)

13.2.6 <u>Charges for Additional Labor</u> (Cont'd)

The charges for additional labor are as follows: (I

	Additional LaborPeriods	Each Half Hour of Fraction Thereof	
		Installation and Repair Technician	Central Access Tandem Maintenance Technician
(C)	Testing and Maintenance with Exchange Telephone Companies, or Other Labor		
	- Basic Time, regularly scheduled working hours, per technician	\$45.00	\$45.00
	 Overtime, outside of regularly scheduled working hours on a scheduled work day, per technician 	\$90.00	\$90.00
	 Premium Time, outside of scheduled work day, per technician 	\$90.00	\$90.00 (I)

13.3 Miscellaneous Services

13.3.1 Maintenance of Service

(A) When a customer reports a trouble to KINI for clearance and no trouble is found in KINI's facilities, the customer shall be responsible for payment of a Maintenance of Service charge for the period of time from when KINI personnel are dispatched to the customer point of inter-

connection to when the work is completed. Failure of KINI personnel to find trouble in

15. <u>Interface Groups, Transmission Specifications and Channel</u> Interfaces (Cont'd)

15.1 <u>Switched Transport Interface Groups</u> (Cont'd)

15.1.11 <u>Available Premises Interface Codes</u>

Following is a matrix showing, for each Interface Group, which premises interface codes are available as a function of KINI's switch supervisory signaling and Feature Group. For explanations of these codes, see the Glossary of Channel Interface Codes in 15.3 following.

Interface <u>Group</u>	Telephone Company Switch Supervisory Signaling	Premises <u>Interface Code</u>	Feature Group D (C)
1	LO LO GO GO LO, GO, LO, GO, LO, GO, LO, GO, LO, GO, RV, EA, EB, EC	2LS2 2LS3 2GS2 2GS3 2DX3 4EA3-E 4EA3-M 6EB3-E 6EB3-M 2DX3 4EA3-E 4EA3-M 6EB3-E 6EB3-M 6EB3-E 6EB3-M 6EC3 2RV3-0 2RV3-T	X X X X X X X
2	LO, GO LO, GO LO LO GO GO GO LO, GO LO, GO LO, GO	4SF2 4SF3 4LS2 4LS3 6LS2 4GS2 4GS3 6GS2 4DX2 4DX3 6EA2-E	(C)

Issued: September 24, 1999 Effective: October 9, 1999

Robert Mater, Director Engineering Operations 621 Westport Boulevard Salina, Kansas 67401

15. <u>Interface Groups, Transmission Specifications and Channel</u> Interfaces (Cont'd)

15.1 <u>Local Transport Interface Groups</u> (Cont'd)

15.1.11 <u>Available Premises Interface Codes</u> (Cont'd)

Interface	Telephone Company	Premises	Feature Group
Group	Switch Supervisory Signaling	<u>Interface Code</u>	(C)
2 (Cont'd) LO, GO	6EA2-M	
Z (COIIC U	LO, GO	8EB2-E	
	LO, GO	8EB2-M	
	LO, GO	6EX2-B	
	RV, EA, EB, EC	4SF2	X
	RV, EA, EB, EC	4DX2	X
	RV, EA, EB, EC	6EA2-E	X
	RV, EA, EB, EC	6EA2-M	X
	RV, EA, EB, EC	8EB2-E	X
	RV, EA, EB, EC	8EB2-M	X
	EA, EB, EC	8EC2-M	X
	RV	4RV2-0	X
	RV	4RV2-T	X
	200	11(12 1	
3	LO, GO	4AH5-B	
_	RV, EA, EB, EC	4AH5-B	Х
	, , , ,		
4	LO, GO	4AH6-C	
	RV, EA, EB, EC	4AH6-C	X
5	LO, GO	4AH6-D	
	RV, EA, EB, EC	4AH6-D	X
6	LO, GO	4DS9-15	
	LO, GO	4DS9-15L	
	RV, EA, EB, EC	4DS9-15	X
	RV, EA, EB, EC	4DS9-15L	X
7	LO, GO	4DS9-31	
	LO, GO	4DS9-31L	
	RV, EA, EB, EC	4DS9-31	X
	RV, EA, EB, EC	4DS9-31L	X
0	TO GO	4D00 62	
8	LO, GO	4DSO-63	
	LO, GO	4DSO-63L	

Issued: September 24, 1999 Effective: October 9, 1999

Robert Mater, Director Engineering Operations 621 Westport Boulevard Salina, Kansas 67401 RV, EA, EB, EC RV, EA, EB, EC 4DSO-63L

X X

(C)

15. <u>Interface Groups, Transmission Specifications and Channel Interfaces</u> (Cont'd)

15.1 <u>Switched Transport Interface Groups</u> (Cont'd)

15.1.11 <u>Available Premises Interface Codes</u> (Cont'd)

Interface	Telephone Company	Premises	Feature Group D (C)
<u>Group</u>	Switching Supervisory Signaling	<u>Interface Code</u>	
9	LO, GO LO, GO RV, EA, EB, EC	4DS6-44 4DS6-44L 4DS6-44 4DS6-44L	X X
10	RV, EA, EB, EC LO, GO LO, GO	4DS6-27 4DS6-27L	A
	RV, EA, EB, EC	4DS6-27	X
	RV, EA, EB, EC	4DS6-27L	X (C)

15.1.12 Supervisory Signaling

- For Interface Groups 1 and 2

DX Supervisory Signaling, E&M Type I Supervisory Signaling, E&M Type II Supervisory Signaling, or E&M Type III Supervisory Signaling

- For Interface Group 2

SF Supervisory Signaling, or Tandem Supervisory Signaling

- For Interface Groups 3 through 5

 Optional Supervisory Signaling Not Available
- For Interface Groups 6 through 10

 These Interface Groups may, at the option of the

customer, be provided with individual transmission path SF supervisory signaling where such signaling is available in Routing Exchange Carriers' central offices. Generally such signaling is available

- 15. <u>Interface Groups, Transmission Specifications and Channel</u> Interfaces (Cont'd)
 - 15.2 <u>Transmission Specifications Switched Access Service</u> (Cont'd)
 - 15.2.1 Standard Transmission Specifications (Cont'd)
 - (B) Type B Transmission Specifications (Cont'd)
 - (5) <u>Echo Control</u> (Cont'd)

Loss for FGD, and expressed as Echo Return Loss (ERL) and Singing Return Loss (SRL) also differ by Feature Group. They are greater than or equal to the following:

Echo	Singing	
<u>Return Loss</u>	<u>Return Loss</u>	
8 dB	4 dB	(C)
o ab	ı ab	()

(6) Standard Return Loss

Standard Return Loss, expressed as Echo Return Loss and Singing Return Loss, on two-wire ports of a four-wire point of termination shall be equal to or greater than:

Echo Return Loss Singing Return Loss

5 dB 2.5 dB

(C) Type C Transmission Specifications

Type C Transmission Specifications are provided with the following parameters:

(1) Loss Deviation

The maximum Loss Deviation of the 1004 Hz loss relative to the Expected Measured Loss (EML) is + 3.0 dB.

(2) <u>Attenuation Distortion</u>

The maximum Attenuation Distortion in the 404 to 2804 Hz frequency band relative to loss at 1004 Hz is -2.0 dB to +5.5 dB.